

Vol. \_\_\_\_\_

## **FINAL REPORT**

**Virucidal Effectiveness Test  
Canine parvovirus  
Using unglazed, clay tiles**

**Test Agent System:  
Dry Steam Vapor System, 2400 Series,  
TANCS® Equipped**

**Data Requirements**

**EPA Guidelines 810.2100 (g)**

**Author**

**Lauren A. Blaszak**

**Study Completion Date**

**pending**

**Performing Laboratory**

**MICROBIOTEST  
105 Carpenter Drive  
Sterling, Virginia 20164**

**MICROBIOTEST Project Identification Number**

**567-105**

**Submitted to: Advanced Vapor Technologies, LLC  
7719 230<sup>th</sup> Street, SW  
Edmonds, WA 98026**

### STATEMENT OF NO DATA CONFIDENTIALITY

Title: Virucidal Effectiveness Test – Canine parvovirus - Using unglazed, clay tiles

Performed by: MICROBIOTEST 105 Carpenter Drive Sterling, Virginia 20164	Sponsor: Advanced Vapor Technologies, LLC 7719 230 <sup>th</sup> Street, SW Edmonds, WA 98026
-------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------

No claim of confidentiality is made for any information contained in this study on the basis of its falling within the scope of FIFRA § 10(d)(1)(A), (B) or (C).

Company Agent

\_\_\_\_\_  
Name

\_\_\_\_\_  
Title

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Date



### QUALITY ASSURANCE UNIT STATEMENT

Title of Study: Virucidal Effectiveness Test – Canine parvovirus - Using unglazed, clay tiles

The Quality Assurance Unit of MICROBIOTEST has inspected the Project Number 567-105 in compliance with current Good Laboratory Practice regulations, (40 CFR § 160).

The dates that inspections were made and the dates that findings were reported to management and to the study director are listed below.

<u>PHASE INSPECTED</u>	<u>DATE OF INSPECTION</u>	<u>DATE REPORTED TO STUDY DIRECTOR</u>	<u>DATE REPORTED TO MANAGEMENT</u>
Protocol	11/29/06	12/15/06	12/29/06
In Process	11/29/06	11/29/06	12/29/06
Final Report	12/15/06	12/15/06	12/29/06

  

_____ Nathan S. Jones, RQAP–GLP Manager, Quality Assurance Unit	_____ Date
-----------------------------------------------------------------------	---------------

## TABLE OF CONTENTS

FINAL REPORT - COVER PAGE .....	1
STATEMENT OF NO DATA CONFIDENTIALITY .....	2
COMPLIANCE STATEMENT .....	3
QUALITY ASSURANCE UNIT STATEMENT .....	4
TABLE OF CONTENTS .....	5
TEST SUMMARY .....	6
TEST CONDITIONS .....	7
STUDY DATES AND FACILITIES .....	8
RECORDS TO BE MAINTAINED .....	8
RESULTS .....	8 - 10
CONCLUSIONS .....	10
APPENDIX I .....	
APPENDIX II .....	

## TEST SUMMARY

**TITLE:** Virucidal Effectiveness Test – Canine parvovirus – Using unglazed, clay tiles

**STUDY DESIGN:** This study was performed according to the signed protocol and project sheets issued by the Study Director.

See Project Sheets (Appendix I)

See signed protocol (Appendix II)

### TEST MATERIALS SUPPLIED BY THE SPONSOR OF THE STUDY:

Dry Steam Vapor System, 2400 series, TANCS® equipped, Serial No. 5505053936, received at MICROBIOTEST 09/28/06, and assigned DS No. 8432.

Note: The Dry Steam Vapor System equipment was operated by a representative of the sponsor.

Note: the 6cm x 6cm x 1.2cm tiles were received by the sponsor on 11/16/06.

**SPONSOR:** Advanced Vapor Technologies, LLC  
7719 230<sup>th</sup> Street, SW  
Edmonds, WA 98026

## TEST CONDITIONS

### Challenge virus:

Canine parvovirus (NIKE/CPV-2b), American BioResearch Laboratories

### Host:

CrFK cells, American BioResearch Laboratories

### Organic load:

Viral stock contained  $\geq 5\%$  organic load

### Active ingredient in test product:

Dry steam vapor generated from tap water

### Contact time:

The Dry Steam Vapor System was operated by a representative of the sponsor to treat the test tiles for a contact time of 7 seconds. The nozzle brush was held over the tile and gently moved in a back and forth motion.

### Contact temperature:

Ambient temperature (22C)

### Dilution:

Ready to use

### Tile Inoculation:

A marked 4 × 4 centimeter area of the smooth surface of unglazed clay test tiles (approximately 6 × 6 × 1.2 centimeters) was inoculated with 0.2mL viral stock and dried for 20 minutes at 22C.

### Media and reagents:

RPMI 1640 containing 5% Newborn calf serum

Phosphate Buffered saline (PBS)

80% acetone

PBS containing 0.5% fetal bovine serum

CPV direct FA conjugate

Tap water

## **STUDY DATES AND FACILITIES**

The laboratory phase of this test was performed at MICROBIOTEST, 105 Carpenter Drive, Sterling, VA 20164, from 11/29/06 to 12/11/06. The study director signed the protocol 11/29/06. The study completion date is the date the study director signed the final report.

All changes or revisions of the protocol were documented, signed by the study director, dated and maintained with the protocol.

## **RECORDS TO BE MAINTAINED**

All testing data, protocol, protocol modifications, test material records, the final report, and correspondence between MICROBIOTEST and the sponsor will be stored in the archives at MICROBIOTEST, 105 Carpenter Drive, Sterling, VA 20164, or at a controlled facility off site.

## **RESULTS**

Results are presented in Tables 1 – 4. The 50% fluorescent focus forming unit dose per mL (FFFUD<sub>50</sub>/mL) was determined from the test and relevant control data using the method of Reed and Muench, Am. J. of Hyg. 1938, 27:493. The cell viability control demonstrated cell viability and media sterility. Virus was not detected in the cell viability control. All controls including cytotoxicity and tile recovery titer met the criteria required for a valid test. Infectious virus was not detected in the host system after exposure to the test agent as described.

The log<sub>10</sub> reduction (LR) was calculated in the following manner:

Log<sub>10</sub> reduction = Infectious virus titer recovered from tile recovery control - Infectious virus titer recovered from test



**RESULTS (continued)**

Table 1  
 Test Results

Dilution	Dry Steam Vapor System, 2400 Series, TANCS® equipped	
	TILE 1	TILE 2
10 <sup>-2</sup>	0 0 0 0	0 0 0 0
10 <sup>-3</sup>	0 0 0 0	0 0 0 0
10 <sup>-4</sup>	0 0 0 0	0 0 0 0
10 <sup>-5</sup>	0 0 0 0	0 0 0 0
10 <sup>-6</sup>	0 0 0 0	0 0 0 0
10 <sup>-7</sup>	0 0 0 0	0 0 0 0
FFFUD <sub>50</sub> /mL	≤10 <sup>1.50</sup>	≤10 <sup>1.50</sup>

Table 2  
 Cytotoxicity Control

Dilution	Dry Steam Vapor System, 2400 Series, TANCS® equipped
	Cytotoxicity Control
10 <sup>-2</sup>	0 0 0 0
10 <sup>-3</sup>	0 0 0 0
10 <sup>-4</sup>	0 0 0 0

Table 3  
 Control results

Dilution	Canine parvovirus Tile Recovery Control
10 <sup>-2</sup>	+ + + +
10 <sup>-3</sup>	+ + + +
10 <sup>-4</sup>	+ + + +
10 <sup>-5</sup>	+ 0 + 0
10 <sup>-6</sup>	0 0 0 0
10 <sup>-7</sup>	0 0 0 0
FFFUD <sub>50</sub> /mL	10 <sup>5.00</sup>

Cell Viability Control
0 0 0 0

Key: + = Canine parvovirus infected cells were detected, fluorescence observed  
 0 = Canine parvovirus infected cells not detected, no fluorescence observed; no cytotoxicity observed

## RESULTS (continued)

Table 4  
Log<sub>10</sub> Reduction

Dry Steam Vapor System, 2400 series, TANCS® equipped	
TILE 1	TILE 2
≥3.50	≥3.50

## CONCLUSIONS

When tested as described, Dry Steam Vapor system, 2400 series, TANCS® equipped, passed the Virucidal Effectiveness Test when Canine parvovirus, containing at least 5% organic load, was exposed to the test agent for 7 seconds at 22C. All of the controls met the criteria for a valid test. These conclusions are based on observed data.